



Buzil® Laundry Compact L 810

Highly concentrated liquid detergent



Area of application

- For the commercial sector
- For all washing temperatures
- For all water hardness ranges
- Suitable for cotton, microfibre, viscose, polyester, polyamide, polypropylene

Product properties

- Efficient, powerful surfactant system for the ultimate removal of dirt
- Optimal lime binding capacity due to special complexing agents
- Perfect whiteness due to optical brighteners
- High dirt holding capacity – therefore dissolved dirt not dragged onto the fibre
- Protection from greying
- Effortlessly removes dirt such as street dirt, soot, grease & oils, urine, etc
- VAH-listed washing process in combination with Buzil® Laundry Bright L 832

Application and dosage

- Washing temperatures from 30°C - 95°C.
- For automatic and manual dosing. The recommended dosage depends on the amount of dirt, the water hardness and the load.
- When processing the laundry according to the RKI list: 2 ml Buz Laundry Compact L 810 and 6 ml Buz Laundry Bright L 832 to 1 liter of liquor at 60 °C and 10 minutes. Exposure time, liquor ratio 1:5, effective range AB
- When processing the laundry according to the VAH list: 2 ml Buz Laundry Compact L 810 and 2 ml Buz Laundry Bright L 832 to 1 liter of liquor at 60 °C and 10 minutes. Exposure time, liquor ratio 1:5



10 - 30 ml / kg
(Dry laundry)



6 ml L 832 + 2 ml L 810/I Flotte
Temperatur: 60 °C



2 ml L 832 + 2 ml L 810/I Flotte
Temperatur: 60 °C

- Textile cleaning: For automatic and manual dosing. The recommended dosage depends on the amount of dirt, the water hardness and the load.

Note

- Please observe the washing and care instructions of the textiles.
- Changes or variations in colour of the product do not impact on the quality. The product image may differ in colour and shape from the original.
- **Safety:** Hazard statements and safety precautions can be found in the relevant safety data sheet, which is available at www.buzil.com.
- **Storage:** Always keep containers closed. Store at room temperature in the original container. Consume opened containers within 9 months.
- **Environmental:** Feed residual emptied containers to the dual system. For detailed information see environmental information.

Further information

- **Product colour:** light yellow - yellow
- **UFI code:** 2K70-Q0JH-N00T-1SD2
- For professional use only.

Sales units

- L810-0020RA: 1 x 20 l canister
- L810-0200RA : 1 x 200 l Drum
- L810-0010RA: 1 x 10 l canister
- L810-0002VL: 4 x 2 l bottle



Remark: Some products may not be available in all territories. Please talk to your customer service representative.

The data in our product information sheets are based on our experience and careful investigations, and correspond to our present state of knowledge. We are, however, not able to examine and influence in detail the varying conditions for usage and materials, and those at premises where products are to be used. For this reason, we can only provide general information on usage. The quality of the work depends on expert assessment of the premises where products are to be used and how they are in fact employed by the user. In the case of doubt, the latter is obliged at all times to test the compatibility of the material to be treated with the Buzil product on an inconspicuous area or to obtain relevant advice on application technology. Liability for incomplete or incorrect data in our product information sheets shall only be assumed in cases of negligence caused by gross negligence or intent; any claims arising from the Product Liability Act shall remain unaffected. All previous product information shall lose its validity through the above listed product information.