

Indumaster® Step **IR 16**

Neutral and material-compatible industrial cleaner













Area of application

- For use in the industrial and workshop sector
- All water-resistant surfaces and floor coverings
- Aluminium surfaces
- Suitable for acrylic glass (PMMA)
- Can be used for mechanical cleaning of escalators and moving walkways
- Suitable for facade cleaning of organically coated uni-coloured metal facades, organically metallic-effect coated metal facades, stainless steel metal facades and plastic facades

Product properties

- Fast-acting power cleaner for manual and machine cleaning
- Good dirt-removing capacity
- Removes oil and grease-containing dirt
- Very good wetting capacity
- Very good material compatibility
- Quality-assured facade cleaning according to RAL-GZ 632

Application and dosage

- Always use cold water.
- In case of heavy foaming in the dirty water tank, Buz® Defoam G 478 can be used.
- Consumption: 0,03 0,24 ml / per m²



/ 10 I water









ml water



10 I water with water

Note

- When used in the machine, the tanks should be cleaned and rinsed regularly
- Changes or variations in colour of the product do not impact on the quality. The product image may differ in colour and shape from the original.
- Safety: Hazard statements and safety precautions can be found in the relevant safety data sheet, which is available at www.buzil.com.
- Storage: Always keep containers closed. Store at room temperature in the original container. Consume opened containers within 9 months.
- Environmental: Feed residual emptied containers to the dual system. For detailed information see environmental information.

Further information

- Product colour: colourless light yellow
- Ingredients according to the EU Detergents Regulation (Det-VO*): AQUA, TETRAPOTASSIUM PYROPHOSPHATE, ALCOHOL, PHENOXYETHANOL, COCAMIDOPROPYL BETAINE, COCAMINE OXIDE, SODIUM CHLORIDE, POTASSIUM METHYLPHOSPHATE, MEK, BENZYL ALCOHOL, PARFUM, BENZISOTHIAZOLINONE, OCTYLISOTHIAZOLINONE, CITRAL, LIMONENE

• GISBAU code: GU 80

■ UFI code: 0J60-N08R-Y00V-3PD9

Sales units

■ IR16-0200RA: 1 x 200 | Drum

■ IR16-0950RA: 1 x 950 I IBC container

■ IR16-0001RA: 12 x 1 l bottle ■ IR16-0010RA: 1 x 10 l canister

 Apply fresh application solutions and consume them within 24 hours at the latest



* A database of correspondences between INCI names, European Pharmacopoeia names and CAS numbers is provided on the European Commission Pharmacos website: https://ec.europa.eu/growth/

* A database of correspondences between INCI names, European Pharmacopoeia names and CAS numbers is provided on the European Commission Pharmacos website: https://ec.europa.eu/growth/tools-databases/cosing/ Remark: Some products may not be available in all territories. Please talk to your customer service representative.

The data in our product information sheets are based on our experience and careful investigations, and correspond to our present state of knowledge. We are, however, not able to examine and influence in detail the varying conditions for usage and materials, and those at premises where products are to be used. For this reason, we can only provide general information on usage. The quality of the work depends on expert assessment of the premises where products are to be used and how they are in fact employed by the user. In the case of doubt, the latter is obliged at all times to test the compatibility of the material to be treated with the Buzil product on an inconspicuous area or to obtain relevant advice on application technology. Liability for incomplete or incorrect data in our product information sheets shall only be assumed in cases of negligence caused by gross negligence or intent, any claims arising from the Product Liability Act shall remain unaffected. All previous product information shall lose its validity through the above listed product information.

