

Safety Data Sheet

according to UK REACH Regulation



CORRIDOR® POWER STRIPPER

S708

Revision date: 03.01.2022

Page 1 of 11

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

CORRIDOR® POWER STRIPPER

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture

EuPCS: PC-CLN-13.3 Floor stripper

Process categories [PROC]: 8, 10

1.3. Details of the supplier of the safety data sheet

Company name: BUZIL-WERK Wagner GmbH & Co. KG
Street: Fraunhofer Str. 17
Place: D-87700 Memmingen
Telephone: +49 (0) 8331 930-6
e-mail: info@buzil.de
Contact person: info@buzil.de
Internet: www.buzil.com

Telefax: +49 (0) 8331 930-880

1.4. Emergency telephone number: +49 (0) 8331 930-6 (08:00 - 16:00 h)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

GB CLP Regulation

Hazard categories:

Serious eye damage/eye irritation: Eye Dam. 1

Hazard Statements:

Causes serious eye damage.

The product does not support combustion. It therefore needs not to be classified as flammable despite a flash point below 60 °C.

2.2. Label elements

GB CLP Regulation

Hazard components for labelling

Sodium Diisooctyl Sulfosuccinate

Signal word: Danger

Pictograms:



Hazard statements

H318 Causes serious eye damage.

Precautionary statements

P280 Wear protective gloves/protective clothing/eye protection/face protection.
P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P310 Immediately call a POISON CENTER/doctor.

2.3. Other hazards

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

SECTION 3: Composition/information on ingredients

Safety Data Sheet

according to UK REACH Regulation



CORRIDOR® POWER STRIPPER

S708

Revision date: 03.01.2022

Page 2 of 11

3.2. Mixtures

Hazardous components

CAS No	Chemical name			Quantity
	EC No	Index No	REACH No	
	GHS Classification			
112-34-5	2-(2-butoxyethoxy)ethanol, diethylene glycol monobutyl ether			20 - < 25 %
	203-961-6	603-096-00-8	01-2119475104-44	
	Eye Irrit. 2; H319			
100-51-6	benzyl alcohol			15 - < 20 %
	202-859-9	603-057-00-5	01-2119492630-38	
	Acute Tox. 4, Acute Tox. 4; H332 H302			
64-17-5	ethanol			10 - < 15 %
	200-578-6	603-002-00-5	01-2119457610-43	
	Flam. Liq. 2, Eye Irrit. 2; H225 H319			
68439-46-3	fatty alcohol polyethoxylate			1 - < 5 %
	Eye Dam. 1, Aquatic Chronic 3; H318 H412			
142-16-5	Bis (2-ethylhexyl) maleat			< 1 %
	01-2119524002-60			
	STOT RE 2, Aquatic Chronic 1; H373 H410			

Full text of H and EUH statements: see section 16.

Specific Conc. Limits, M-factors and ATE

CAS No	EC No	Chemical name	Quantity
	Specific Conc. Limits, M-factors and ATE		
112-34-5	203-961-6	2-(2-butoxyethoxy)ethanol, diethylene glycol monobutyl ether	20 - < 25 %
	inhalation: LC50 = >20 mg/l (vapours); dermal: LD50 = >2000 mg/kg; oral: LD50 = >2000 mg/kg		
100-51-6	202-859-9	benzyl alcohol	15 - < 20 %
	inhalation: ATE = 11 mg/l (vapours); inhalation: ATE = 1,5 mg/l (dusts or mists); dermal: LD50 = 2000 mg/kg; oral: LD50 = 1230 mg/kg		
64-17-5	200-578-6	ethanol	10 - < 15 %
	inhalation: LC50 = >20 mg/l (vapours); dermal: LD50 = >2000 mg/kg; oral: LD50 = >2000 mg/kg Eye Irrit. 2; H319: >= 50 - 100		
68439-46-3		fatty alcohol polyethoxylate	1 - < 5 %
	inhalation: LC50 = >5 mg/l (dusts or mists); dermal: LD50 = >2000 mg/kg; oral: LD50 = >2000 mg/kg		
142-16-5		Bis (2-ethylhexyl) maleat	< 1 %
	dermal: LD50 = 14000 mg/kg; oral: LD50 = >2000 mg/kg		

Labelling for contents according to Regulation (EC) No 648/2004

< 5 % anionic surfactants, < 5 % non-ionic surfactants, perfumes (Benzyl alcohol, Hexyl cinnamal).

SECTION 4: First aid measures

4.1. Description of first aid measures

After inhalation

Provide fresh air.

After contact with skin

After contact with skin, wash immediately with plenty of water and soap.

Safety Data Sheet

according to UK REACH Regulation



CORRIDOR® POWER STRIPPER

S708

Revision date: 03.01.2022

Page 3 of 11

Take off contaminated clothing and wash it before reuse.

After contact with eyes

Rinse immediately carefully and thoroughly with eye-bath or water.

After ingestion

Rinse mouth immediately and drink plenty of water.

Do NOT induce vomiting.

4.2. Most important symptoms and effects, both acute and delayed

No information available.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

Water spray jet
alcohol resistant foam
Carbon dioxide
Extinguishing powder

Unsuitable extinguishing media

Full water jet

5.2. Special hazards arising from the substance or mixture

Hazardous combustion products:
Carbon dioxide
Carbon monoxide

5.3. Advice for firefighters

Co-ordinate fire-fighting measures to the fire surroundings.

Additional information

Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures

Use personal protection equipment.
Avoid contact with skin, eyes and clothes.

6.2. Environmental precautions

Do not allow to enter into surface water or drains.
Do not allow to enter into soil/subsoil.

6.3. Methods and material for containment and cleaning up

Other information

Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents).
Treat the recovered material as prescribed in the section on waste disposal.

6.4. Reference to other sections

Personal protection equipment: see section 8
Disposal: see section 13

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Safety Data Sheet

according to UK REACH Regulation



CORRIDOR® POWER STRIPPER

S708

Revision date: 03.01.2022

Page 4 of 11

Advice on safe handling

Avoid contact with skin, eyes and clothes.
Do not mix with other chemicals.
Use personal protection equipment.
When using do not eat, drink or smoke.
Use only in well-ventilated areas.
Do not breathe gas/fumes/vapour/spray.

Advice on protection against fire and explosion

No special fire protection measures are necessary.

Advice on general occupational hygiene

Take off contaminated clothing.
Wash hands before breaks and after work.
When using do not eat, drink or smoke.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Keep container tightly closed.

Hints on joint storage

No special measures are necessary.

7.3. Specific end use(s)

There are no data available on the mixture itself.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Exposure limits (EH40)

CAS No	Substance	ppm	mg/m ³	fibres/ml	Category	Origin
112-34-5	2-(2-Butoxyethoxy)ethanol	10	67.5		TWA (8 h)	WEL
		15	101.2		STEL (15 min)	WEL
64-17-5	Ethanol	1000	1920		TWA (8 h)	WEL

8.2. Exposure controls

Individual protection measures, such as personal protective equipment

Eye/face protection

Wear eye/face protection. (EN 166)

Hand protection

Wear suitable gloves. (EN 374, Breakthrough time: >10 min.)

Suitable material: NBR (Nitrile rubber).

Thickness of the glove material $\geq 0,1$ mm

A survey of suitable brands with detailed information on breakthrough times is available upon request.

Diluted ready-to-use solutions $\leq 1\%$:

Protective gloves may be waived, if equivalent measures allowing for an increased skin stress because of wet work are implemented (e. g. application of suitable skin protecting creams).

Skin protection

Wear suitable work clothing.

Respiratory protection

Use only in well-ventilated areas.

In case of inadequate ventilation wear respiratory protection. (DIN EN 14387, A 1)

Safety Data Sheet

according to UK REACH Regulation



CORRIDOR® POWER STRIPPER

S708

Revision date: 03.01.2022

Page 5 of 11

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state:	Liquid
Colour:	colourless
Odour:	Perfumes, fragrances

Test method

Changes in the physical state

Melting point/freezing point:	approx. 0 °C
Boiling point or initial boiling point and boiling range:	approx. 100 °C
Flash point:	48 °C

Flammability

Solid/liquid:	not applicable
Gas:	not applicable
Lower explosion limits:	not determined
Upper explosion limits:	not determined

Self-ignition temperature

Solid:	not applicable
Gas:	not applicable
Decomposition temperature:	not determined

Oxidizing properties

Not oxidising.	
pH-Value (at 20 °C):	9,1 - 9,5
Viscosity / dynamic: (at 25 °C)	< 10 mPa·s (50 1/s)
Water solubility:	completely miscible

Solubility in other solvents

not determined	
Partition coefficient n-octanol/water:	not determined
Vapour pressure:	not determined
Density (at 25 °C):	1,00 g/cm ³
Relative vapour density:	not determined

9.2. Other information

Information with regard to physical hazard classes

Sustaining combustion:	Not sustaining combustion
------------------------	---------------------------

Other safety characteristics

Solid content:	not determined
Evaporation rate:	not determined

Further Information

SECTION 10: Stability and reactivity

10.1. Reactivity

No hazardous reaction when handled and stored according to provisions.

10.2. Chemical stability

Safety Data Sheet

according to UK REACH Regulation



CORRIDOR® POWER STRIPPER

S708

Revision date: 03.01.2022

Page 6 of 11

The product is stable under storage at normal ambient temperatures.

10.3. Possibility of hazardous reactions

No hazardous reaction when handled and stored according to provisions.

10.4. Conditions to avoid

The product is stable under storage at normal ambient temperatures.

10.5. Incompatible materials

No information available.

10.6. Hazardous decomposition products

No known hazardous decomposition products.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in GB CLP Regulation

Acute toxicity

Based on available data, the classification criteria are not met.

CAS No	Chemical name				
	Exposure route	Dose	Species	Source	Method
112-34-5	2-(2-butoxyethoxy)ethanol, diethylene glycol monobutyl ether				
	oral	LD50 >2000 mg/kg	Rat	ATE	
	dermal	LD50 >2000 mg/kg	Rat	ATE	
	inhalation vapour	LC50 >20 mg/l	Rat	ATE	
100-51-6	benzyl alcohol				
	oral	LD50 1230 mg/kg	Rat		
	dermal	LD50 2000 mg/kg	Rabbit		
	inhalation vapour	ATE 11 mg/l			
	inhalation aerosol	ATE 1,5 mg/l			
64-17-5	ethanol				
	oral	LD50 >2000 mg/kg	Rat	ATE	
	dermal	LD50 >2000 mg/kg	Rat	ATE	
	inhalation vapour	LC50 >20 mg/l	Rat	ATE	
68439-46-3	fatty alcohol polyethoxylate				
	oral	LD50 >2000 mg/kg	Rat	OECD 401	
	dermal	LD50 >2000 mg/kg	Rat	ATE	
	inhalation aerosol	LC50 >5 mg/l	Rat	ATE	
142-16-5	Bis (2-ethylhexyl) maleat				
	oral	LD50 >2000 mg/kg	Rat	OECD 401	
	dermal	LD50 14000 mg/kg	Rabbit	ATE	

Safety Data Sheet

according to UK REACH Regulation



CORRIDOR® POWER STRIPPER

S708

Revision date: 03.01.2022

Page 7 of 11

Irritation and corrosivity

Causes serious eye damage.

Skin corrosion/irritation: Based on available data, the classification criteria are not met.

Sensitising effects

Based on available data, the classification criteria are not met.

Carcinogenic/mutagenic/toxic effects for reproduction

Based on available data, the classification criteria are not met.

STOT-single exposure

Based on available data, the classification criteria are not met.

STOT-repeated exposure

Based on available data, the classification criteria are not met.

Aspiration hazard

Based on available data, the classification criteria are not met.

SECTION 12: Ecological information

12.1. Toxicity

Safety Data Sheet

according to UK REACH Regulation



CORRIDOR® POWER STRIPPER

S708

Revision date: 03.01.2022

Page 8 of 11

CAS No	Chemical name					
	Aquatic toxicity	Dose	[h] [d]	Species	Source	Method
112-34-5	2-(2-butoxyethoxy)ethanol, diethylene glycol monobutyl ether					
	Acute fish toxicity	LC50 mg/l	2780	96 h	Pimephales promelas (fathead minnow)	
	Acute algae toxicity	ErC50 mg/l	> 100		Scenedesmus subspicatus	
	Acute crustacea toxicity	EC50 mg/l	4950	48 h	Daphnia magna (Big water flea)	
100-51-6	benzyl alcohol					
	Acute fish toxicity	LC50	460 mg/l	96 h	Pimephales promelas (fathead minnow)	
	Acute algae toxicity	ErC50	640 mg/l	96 h	Scenedesmus quadricauda	
64-17-5	ethanol					
	Acute fish toxicity	LC50 mg/l	>1000	96 h		
	Acute algae toxicity	ErC50 mg/l	>100			
	Acute crustacea toxicity	EC50 mg/l	>1000	48 h		
68439-46-3	fatty alcohol polyethoxylate					
	Acute fish toxicity	LC50 mg/l	1-10	96 h	Danio rerio (zebrafish)	OECD 203
	Acute crustacea toxicity	EC50	0,7 mg/l	48 h	Daphnia magna (Big water flea)	
	Acute bacteria toxicity	(>1000 mg/l)				
142-16-5	Bis (2-ethylhexyl) maleat					
	Acute fish toxicity	LC50 mg/l	>100	96 h	Danio rerio (zebrafish)	Classification according to Directive 67/548/EEC or 1999/45/EC
	Acute algae toxicity	ErC50 mg/l	>0,619	72 h	Pseudokirchneriella subcapitata	OECD 201
	Acute crustacea toxicity	EC50 mg/l	59,5	48 h	Daphnia magna (Big water flea)	OECD 202
	Algae toxicity	NOEC mg/l	0,052	3 d	Pseudokirchneriella subcapitata	OECD 201
	Acute bacteria toxicity	(>1000 mg/l)				
				3 h	Respiratory inhibition of municipal activated sludge.	OECD 209

12.2. Persistence and degradability

The surfactants contained in this mixture comply with the biodegradability criteria as laid down in Regulation (EC) No.648/2004 on detergents.

Safety Data Sheet

according to UK REACH Regulation



CORRIDOR® POWER STRIPPER

S708

Revision date: 03.01.2022

Page 9 of 11

CAS No	Chemical name	Method	Value	d	Source
		Evaluation			
112-34-5	2-(2-butoxyethoxy)ethanol, diethylene glycol monobutyl ether	OECD 301	>60%	28	
	Readily biodegradable (according to OECD criteria).				
100-51-6	benzyl alcohol	OECD 301	>60%	28	
	Readily biodegradable (according to OECD criteria).				
64-17-5	ethanol	OECD 301	>60%	28	
	Readily biodegradable (according to OECD criteria).				
68439-46-3	fatty alcohol polyethoxylate	OECD 301F/ ISO 9408/ EEC 92/69/V, C.4-D	>60%	28	
	Readily biodegradable (according to OECD criteria).				
142-16-5	Bis (2-ethylhexyl) maleat	OECD 301D	>60%	28	
	Readily biodegradable (according to OECD criteria).				

12.3. Bioaccumulative potential

No indication of bioaccumulation potential.

Partition coefficient n-octanol/water

CAS No	Chemical name	Log Pow
112-34-5	2-(2-butoxyethoxy)ethanol, diethylene glycol monobutyl ether	0,56
100-51-6	benzyl alcohol	1,05
142-16-5	Bis (2-ethylhexyl) maleat	7,24

12.4. Mobility in soil

The product has not been tested.

12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

12.7. Other adverse effects

No information available.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Disposal recommendations

Dispose of waste according to applicable legislation.

Delivery to an approved waste disposal company.

List of Wastes Code - residues/unused products

070601 WASTES FROM ORGANIC CHEMICAL PROCESSES; wastes from the MFSU of fats, grease, soaps, detergents, disinfectants and cosmetics; aqueous washing liquids and mother liquors; hazardous waste

List of Wastes Code - contaminated packaging

150102 WASTE PACKAGING; ABSORBENTS, WIPING CLOTHS, FILTER MATERIALS AND PROTECTIVE CLOTHING NOT OTHERWISE SPECIFIED; packaging (including separately collected municipal packaging waste); plastic packaging

Contaminated packaging

Non-contaminated packages may be recycled.

Safety Data Sheet

according to UK REACH Regulation



CORRIDOR® POWER STRIPPER

S708

Revision date: 03.01.2022

Page 10 of 11

SECTION 14: Transport information

Land transport (ADR/RID)

14.1. UN number or ID number: No dangerous good in sense of these transport regulations.

Inland waterways transport (ADN)

14.1. UN number or ID number: No dangerous good in sense of these transport regulations.

Marine transport (IMDG)

14.1. UN number or ID number: No dangerous good in sense of these transport regulations.

Air transport (ICAO-TI/IATA-DGR)

14.1. UN number or ID number: No dangerous good in sense of these transport regulations.

14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: No

14.6. Special precautions for user

No special measures are necessary.

14.7. Maritime transport in bulk according to IMO instruments

not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU regulatory information

Restrictions on use (REACH, annex XVII):

Entry 3, Entry 55

2010/75/EU (VOC): < 30 %

Additional information

Regulation (EC) No. 648/2004 (Detergents regulation)

National regulatory information

Water hazard class (D): 1 - slightly hazardous to water

15.2. Chemical safety assessment

Chemical safety assessments for substances in this mixture were not carried out.

SECTION 16: Other information

Changes

This data sheet contains changes from the previous version in section(s): 2,3,9,14,15.

Abbreviations and acronyms

ADR: Accord européen sur le transport des marchandises dangereuses par Route
(European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonized System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service

LC50: Lethal concentration, 50%

LD50: Lethal dose, 50%

Process categories according to ECHA guidance on information requirements and chemical safety

Safety Data Sheet

according to UK REACH Regulation



CORRIDOR® POWER STRIPPER

S708

Revision date: 03.01.2022

Page 11 of 11

assessment, chapter R.12:

PROC 1: Use in closed processes.

PROC 2: Chemical production or refinery in closed continuous process with occasional controlled exposure or processes with equivalent containment conditions

PROC 4: Chemical production where opportunity for exposure arises

PROC 7: Industrial spraying

PROC 8 (Transfer): Dilution of concentrated products, application of drain cleaners, dosage of textile washing agents.

PROC 9: Transfer of substance or mixture into small containers (dedicated filling line, including weighing)

PROC 10 (Roller application or brushing): Processing without large-scale spraying.

PROC 11 (Spraying outside industrial settings): Processing with large-scale spraying (e. g. high pressure cleaning, foam gun).

PROC 13: Treatment of articles by dipping and pouring

PROC 19 (Hand-mixing with intimate contact): Hand cleaning and disinfection

Relevant H and EUH statements (number and full text)

H225	Highly flammable liquid and vapour.
H302	Harmful if swallowed.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H373	May cause damage to organs through prolonged or repeated exposure.
H410	Very toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.

Further Information

Classification for mixtures and used evaluation method according to regulation (EC) No 1272/2008 [CLP]: 9 (1)

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)